Dart Aerospace Ltd. Wednesday, 03/06/2009 10:48:33 AM User: Julie Dawson **Process Sheet** : CU-DAR001 Dart Helicopters Services Customer -**Drawing Name** : LABEL Job Number : 48350 **Estimate Number** : 10124 : D2258200 P.O. Number **Part Number** D2258 REV ₽1 : 03/06/2009 S.O. No. : This Issue **Drawing Number** Prsht Rev. : NC Project Number : // : PURCHASED PARTS First Issue Type **Drawing Revision Previous Run** : 46323 Material **Due Date** : 15/06/2009 20 Um: Each Qty: Written By Checked & Approved By Comment : Est: B 04.04.15 Reformat; Clarify Step 2 KJ/RF **Additional Product** Job Number: Seq. #: **Machine Or Operation:** Description: PG **PURCHASING** 1.0 **Comment: PURCHASING** C209/06/04 Issue P/0: _89 18 Make D2258-200 read 200lb / 91kg as per Dwg D2258 Material: Red letters (1.00" min height) with adhesive backManufacture from 3M 7mil masking film #8522CP or Avery IPM #2031 Material release note is required D2258200P 2.0 Weight Placard 200lb Comment: Qty.: 1.0000 Each(s)/Unit Total: 20.0000 Each(s) WEIGHT PLACARD 200 LB 3.0 PACKAGING 1 PACKAGING RESOURCE #1 Comment: PACKAGING RESOURCE #1 Receive and Inspect for transit damage Ensure material release note is attached 4.0 QC6 Comment: DIMENSIONAL CHECK PACKAGING 1 PACKAGING RESOURCE #1 5.0 Comment: PACKAGING RESOURCE #1

Identify and Stock

Location:_

ST 505 -

Dart Aerospace Ltd

W/O:	<u> </u>		WO	RK ORDER CHANG	FQ	,,,			
DATE STEP		PRO	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector		
Part No	:	PAR #:	Fault Categ	ory:	NCR: Yes	No DQ	A:	Date:	
Resolution:		olution:	Disposition	_ QA: N/C Cld	QA: N/C Closed: Date:				
NCR:			WORK ORDE	R NON-CONFORMA	NCE (NCR)	· , , ,		
DATE	STEP	Description of NC		Corrective Action Section B		Verification		Approval Chief Eng	Approval QC Inspector
	Section A		Initial Chief Eng	Action Description Chief Eng	iption Sign & Date		on C		
								:	•
],

NOTE: Date & initial all entries

Date:

. Wednesday, 03/06/2009 10:48:33 AM

User: *

Julie Dawson

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: LABEL

Job Number: 48350

Part Number: D2258200

Job Number:



Seq. #:

Machine Or Operation:

Description:

6.0

QC21

FINAL INSPECTION/W/O RELEASE



mg-06-11

Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



Dart Aerospace Ltd

W/O:

DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC inspector
Part No);	PAR #: Fault Category: NC	R: Yes	s No DQ	\ :	Date:	

WORK ORDER CHANGES

Resolution: _____ Disposition: _____ QA: N/C Closed: ____ Date: ____

NCR:			WORK ORDER NON-CONFORMANCE (NCR)								
		Description of NC		Corrective Action Section B			A				
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Verification Section C	Approval Chief Eng	Approval QC Inspector			
					·						
								1.			
					:			,			

NOTE: Date & initial all entries

MAXIMUM DISTRIBUTED LOAD APPROX XXX lb/ YYY kg

8 D2258-XXX PLACARD

PART NUMBER	LCAD
D2258-132	132 lb/60 kg
D2258-160	160 lb/ 73 kg
D2258-170	170 lb/ 77 kg
D2258-200	200 lb/ 91 kg
D2258-220	220 lb/ 100 kg
D2258-300	300 lb/ 136 kg

1) MATERIAL: 1" H GH RED LETTERS, ADHESIVE BACK. MANUFACTURED FROM 3M, 7 MIL MASKING FILM #8522CP OR

AVERY IPM #2031

3) TOLERANCES: PER DART QSI 016 UNLESS OTHERWISE NOTED

4) UNITS: INCHES UNLESS OTHERWISE NOTED

5) BREAK SHARP EDGES: N/A

6) IDENTIFICATION: N/A

8) PART NUMBER = D2258-MAX DISTRIBUTED WEIGHT IN POUNDS (Ibs) OF THE BASKET.

EXAMPLE: D2258-132 IS A BASKET WITH A MAX DISTRIBUTED WEIGHT OF 132 POUNDS (lbs).

REDRAWN, SEE PAR 08-026 ADDED NOTE NEW ISSUE 94.02.28 REV. DESCRIPTION BY DATE DESIGN DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA DRAWN CHECKED DRAWING NO. REV. C D2258 MFG. APPR SHEET 1 OF 1 APPROVEC **SCALE** UTILITY BASKET PLACAR) DE APPR.

08.10.29

Note: For the full product names of the 3M products listed on this page, please see page 1.

Shelf Life and Storage

- 3M ** Scotcheal ** Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges;
 - Original packaging, including plastic wrap
 - Relative humidity of 20% to 80%
 - = Femperature of 33 $^{\circ}$ to $104 ^{\circ}$ F (0 $^{\circ}$ to $40 ^{\circ}$ C)
 - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at http://www.3M.com/msds.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Warranty and Limited Remedies

3M MCS Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose. We warrant graphics produced by a 3M lnk Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.

3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at www.scotchprint.com, or order them via our Faxon-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768

International: 1-651-732-6506

Subject	Bulletin No.	FOD No.
Product Bulletins		
3M Scotchcal Overlaminate 8519 and 8520	8519/8520	4524
Instruction Builetins		
Making thermal ink jet graphics	4.23	6523
Application, substrate selection, preparation and substrate-specific application techniques	5.1	7001
Warranties		
Worldwide 3M ** MCS ** Warranty Packet (includes all Commercial Graphics MCS Wo	et urranties)	9503
Worldwide 3M " MCS " Warranty Overv	iew-Folder	9504

tM. Scotchcal and MCS are trademarks of 3M.
Epson and Stylus Pro are trademarks of Epson.
HP and DesignJet are tradenames of Hewlett Packard.
Soura is a trademark of Swiss Alaminum Ud.
Imron is a registered trademark of DuPont in the United States

Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

3M

Commercial Graphics Division 3M Center, Building 220-6W-06 PO Box 33220 St. Paul, MN 55133-3220 USA General Into 1-800-374-6772 Technical Into 1-800-328-3908 3M Canada P.O. Box 5757 London, Ontario Canada N6A 4T1 1-8(X)-265-1840 Fax 519-452-6245

Eax 1-651-736-4233 Eax-on-Demand 1-800-364-0768 US/Canada or 1-651-732-6506 International Eax-on-Demand document 4506 www.scotchprint.com 3M México, S.A. de C.V.

Av. Santa Fe No. 55 Col Santa Fe, Del Alvaro Obregón México, D.F. 01210 52-55-52-70-04-00 Fax 52-55-52-70-22-77 3M Puerto Rico, Inc. Puerto Rico Industrial Park PO. Box 100 Carolina, PR (0986-0100 787-620-3000 Fax 787-750-3035

93M 2003. All rights reserved.

Product Bulletin 8522 - 3

Product Bulletin 8522

3M

Release F, Effective January 2003 Black bar in margin indicates a change

Scotchcal [™] Opaque Imaging Media 8522

Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

Advantages

- Optimized for use with selected Epson Stylus Proprinters and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media:
 - For opaque (reflective) graphics -
 - Changeable, easy to remove from warranted substrates up to 1 year later
 - Dries quickly after printing so the overlaminate can be applied almost immediately
 - Low slippage paper liner for superior tiling
- Overlaminates:
 - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
 - Available in luster and matte gloss
 - Adhesive allows for heat-assisted or cold-temperature lamination

Applications and Uses

3M [∞] Scotchcal [∞] Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M [∞] MCS [∞] Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics

- Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivers, used in vertical (± 10°) applications

Limitations of End Uses

The following uses and applications are specifically NOT warranted.

- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallboard
- Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication. Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products and Equipment

Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
 - Epson Archival Inks
- Epson Stylus Pro 10600 printer
 - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
 - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
 - HP83UV Color Ink System

Overlaminates (required)

- 3M[™] Luster Overlaminate 8519 (semi-gloss)
- 3M [™] Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Glass
- Imron ® (polyurethane-painted metal panel)
- Acrylic
- Sintra board

Test and Approve Non-warranted Substrates Before

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates, 3M recommends that you test and approve the media for both adhesion and removal characteristics.

Characteristics

Characteristic	Description				
Media	7 mil, white, opaque graphic film				
Liner	Low-slippage, lay flat paper				
Adhesive	Changeable, pressure sensitive				
Thickness (media and adhesive)	7.5 to 8 mil (nominal)				
Application substrates	See Warranted Substrates, above				
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)				
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)				
Roll sizes	36" x 45 feet (914 mm x 13.5 m) 54" x 45 feet (1372 mm x 13.5 m)				

How to Become a 3M Ink Jet Registered Fabricator

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at www. scotchprint.com

Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

Warranted Durability

Media 8522	Epson Pr	inters	HP Printers		
with Overlaminate 8519 or 8520	Outdoor	Indoor	Outdoor	Indoor	
Applied to Warranted Substrates	2 years	5 years	3 years	5 years	

Removability

Imaging media 8522 is removable from warranted substrates for 1 year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

Fabrication

Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

Graphic Construction Options

Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source	
	Overlaminate 8519, 8520 Adhesive on bottom
	Imaging Media 8522 Image on top; adhesive on botton
	Opeque Substrate



VENDU À:

SOLD TO:

Dart Aerospace Ltd

Hawkesbury, Ontario K6A 1K7

1270 Aberdeen

210 MAIN W., HAWKESBURY, ONT. K6A 2H6

Tel.: 613 632-2001 Fax: 613 632-9491

www.studiolettrage.com

INVOICE / FACTURE

No.:

12221

DATE:

PAGE

06/10/2009

1 of 1 Re: Quote No. 7071

Dart Aerospace Ltd

LIVRÉ À: SHIPPED TO:

Hawkesbury, Ontario

ITEM ARTICLE	QTY QYÉ	UNIT UNITÉ	DESCRIPTION	GST TPS	PST TVP	UNIT PRICE	AMOUN
		20	D2258200P set up printing G - GST @ 5%; PST @ 8% GST	G	TVP	UNIT PRICE PRIX UNITÉ 2.50 100.00	50.00 100.00
		C 4/4/10	PST Exempt: #6122-5207				7.50
							ļ
Studio de Lettrage GS PO 8918	T #869034	678RP001			•	TOTAL	
Sold By:							57.50

Dart Aerospace Ltd

W/O:			WO	RK ORDER CHANG	ES					
DATE	STEP	PR	PROCEDURE CHANGE					Approval Chief Eng / Prod Mgr	Approval QC Inspector	
Part No: PAR #:		PAR #:	Fault Categ	ory:	NCR: Yes No DQ			QA: Date:		
		Disposition: Q			QA: N/C Closed:					
NCR:			WORK ORDE	R NON-CONFORMA	NCE (NC	R)				
DATE	STEP	Description of NC Section A	Corrective Action Initial Action Descript Chief Eng Chief Eng		on B Sign Date	& Sect	cation ion C	Approval Chief Eng	Approval QC Inspector	
			Sillor Elig	Office Ling	Date					
					•					

NOTE: Date & initial all entries